

UNDERGROUND PIPE FOR WASTE WATER

Derakane Epoxy Vinyl Ester Resins – Case History



Location / Year

Installed in 1978 at Abu Dhabi National Oil Co. (ADNOC).

Fabricator

Protesa, Spain.
Engineering company : Snamprogetti, Milano.

Fabrication

Hand lay-up with **DERAKANE 411** epoxy vinyl ester resin.

Technical Data

DN 100 to 600 (4 in to 23.6 in)
Length 10 km (6.2 mi)
Maximum pressure 7.9 bar (115 psi).

Service Conditions

Underground pipe for waste water, seawater cooling lines and desalinated water in a refinery.

Last update in 1987.

NOTICE : No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN ; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.



Ashland is committed to the continuous evolution of technology and service solutions that promote health, safety and environmental protection around the world. © Registered trademark and ™ trademark of Ashland Inc.
* Registered service mark of the American Chemistry Council, © 2009 Ashland
<http://www.ashland.com>, <http://www.derakane.com>