

ADDpoxy® 828

Unmodified liquid Epoxy Resins

General ADDpoxy® 828 is a general purpose unmodified epoxy resin based on Bisphenol A with medium viscosity.

Applications ADDpoxy® 828 is widely used in 2-pack amine, polyaminoamide and heat (acid) cured formulation. The main application are in highly chemical resistant coatings, civil engineering, matrix adhesives, composites as well as in the fields of electrical insulation and filament winding for manufacturing large diameter pipes.

- Properties**
- Medium viscosity and high reactivity
 - Compatible with various hardeners, reactive diluents and accelerators
 - Low hydrolysable chlorine content and therefore slight tendency to crystallise at low temperature.
 - Conforms to FDA listing (food additives)

The resins formulated yield:

- Superior mechanical and electrical properties
- Excellent chemical and water resistance

Specific Key Data	Property	Value	Test method
	Appearance	Clear, no contamination	JCTM 001
	Colour APHA	100 max.	ASTM D-1209
	Epoxy value	5.20 - 5.49 eq/Kg	ASTM D-1652
	Weight per epoxide	182 - 192 g/eq	ASTM D-1652
	Viscosity at 25°C (77°F)	11,000 - 14,000 mPa.S	ISO 12058-1
	Hydrolysable Chlorine	<500 ppm	JCTM 195
	Water Content (KF)	0.08% max.	ASTM D-4017

Specific key data are individually checked throughout, guaranteed and included in certificate of analysis.

Typical Key Data	Property	Value	Test method
	Residual Epichlorohydrin	5.0 ppm max	JCTM GC6010
	Density at 25°C	1.16 g/cm ³	ISO 1675
	Flash point	≥ 200°C	ISO 2719

Typical key data are spot checked; the values are typical for the product and are indicated for information only. The values are not included in certificate of analysis.

As-supplied form	Liquid
Odour	None
Shelf life (at storage temperature between 10-50°C) (See expiry date on original container)	Several years
Hazardous decomposition products (When disposed of in fire)	Carbon monoxide, carbon dioxide and other toxic gases and vapours.
Disposal	Regular procedures approved by local authorities.

Packaging and Storage ADDpoxy® 828 is supplied in bulk and in 240 kg steel drums. This product has a minimum shelf life of four years when stored in unopened sealed containers in a dry location at room temperature. Like most liquid epoxy resins, ADDpoxy® 828 may crystallise when stored below room temperature. Heating the resin to 60-70°C (140-160°F), for several hours will re-liquefy it and restore its original properties.

**Handling/Safety
Precautions**

Warning: Causes irritation.

May cause allergic skin reaction.

Avoid contact with eyes, skin or clothing.

Avoid breathing vapour, mist or spray.

Use with adequate ventilation.

Promptly remove wet, contaminated clothing and wash before reuse.

Wash after handling.

Store in a cool, dry area in closed containers.

Please read Material Safety Data Sheet before using.

Note

ADDpoxy® is a registered trademark of JANA or an affiliate thereof.

Jubail Chemical Industries Co. (JANA)

P.O Box 11919

Jubail Industrial city 31961

Kingdom of Saudi Arabia

Tel : +966 3 3478888

Fax : +966 3 3476705

DISCLAIMER:

THE INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE BASED UPON OUR DATA BELIEVED TO BE CORRECT. HOWEVER, SINCE THE CONDITIONS OF USE ARE BEYOND OUR CONTROL, NO GUARANTEE OR WARRANTY OF ANY KIND, EXPRESSED OR IMPLIED IS MADE WITH RESPECT TO THE INFORMATION CONTAINED HEREIN.

**ADD RESINS BRANCHES AT:
JOHANNESBURG / DURBAN / CAPE TOWN**

addresins.com