

## CANOPY COAT GREY

### GENERAL DESCRIPTION

Ultra Matt Grey spray or brush applied coating designed for application to the interior of fibreglass canopies or panels

### USES AND PROPERTIES

High opacity matt grey finish

Low VOC product incorporating 25% recycled material

Formulated for spray application

Usually spotted with Canopy Coat Black (474 077) and Canopy Coat White (474001) wet on wet

### TECHNICAL DATA

Binder Type	:	Acrylic Co Polymer
Drying Time	:	Surface Dry: 1hour (at 23°C and 50% humidity) Hard Dry: 4 hours (at 23°C and 50% humidity)
Drying Process	:	Water evaporation followed by coalescence
Overcoating	:	2- 4 hours
Viscosity	:	90 – 95ku
Specific Gravity	:	1,19 ±0,05kg/ltr
Non Volatile Content	:	Mass: 35%±3%
Volume	:	23%±3%
Gloss	:	Ultra Matt
Coverage	:	3-5m <sup>2</sup> /ltr (76 - 46µ Dry Film Thickness)
Flash Point	:	Not Applicable
Application Temp	:	>4°C <40°C
Colour Range	:	Grey Only
Clean Equipment With	:	Water
Pack Sizes	:	20 litre

Technical data based on Canopy Coat Grey Code: 474002.

Coverage/spreading rate of **Canopy Coat Grey** depends largely on the conditions and application equipment being used.

## **APPLICATION**

Correct surface preparation is essential for good product performance and all surfaces should be free of any loose and friable materials, or any grease, oils, release agents or any other substance that may affect adhesion.

Most canopies being sprayed tend to be recently manufactured and the usual preparation procedures must be followed.

Do not apply when ambient temperatures are  $<4^{\circ}\text{C}$  or  $>40^{\circ}\text{C}$ .

Thoroughly stir the Canopy Coat Grey and apply, as supplied, 1 coat of **Canopy Coat Grey** by spray at the specified spread rate. Then, while still wet splatter with Canopy Coat White and Canopy Coat Black to achieve the required finish.

## **SAFETY INSTRUCTIONS**

Always keep out of reach of children and animals.

Wear a suitable dust mask and goggles when preparing surfaces.

Ensure good ventilation during application and drying.

If accidental contact with skin, wash immediately with soap and water or a recognised skin cleaner.

If accidental contact with eyes, rinse immediately with plenty of water and seek medical advice.

Harmful if swallowed. Seek medical attention and do not induce vomiting.

## **GENERAL**

Varying environmental conditions and film thicknesses will affect opacity and drying times.

It is therefore recommended that you contact a Add resins Sales representative for advice on all your painting requirements whenever possible.

## **PREVENTING PROBLEMS AND GENERAL INFORMATION**

The ambient temperature must be between  $4^{\circ}\text{C}$  and  $40^{\circ}\text{C}$  and humidity between 10% and 85%.

Excessive application thickness and/or rapid drying could lead to mud cracking.

Avoid applying under adverse weather conditions as this could result in poor product performance.

Work from corner to corner, or from a natural cut off point to another.

Do not attempt touch ups, but redo complete panels.

Always keep a wet edge and avoid downing tools during the application process to prevent lap marks and variances in colour or texture.

To ensure consistent appearance ensure that the batch numbers on all containers used are the same. Where batch numbers on containers differ, intermix containers before use.

**CLEANING, STORAGE AND DISPOSAL**

Remove as much paint as possible from application equipment and wash immediately after use with water. Close containers tightly after use and store in a cool well-ventilated area.

Do not empty contents or wash water into drains or water courses.

When disposing please follow local authorities regulations and recycle the container after use.

The technical data furnished is given to the best of our knowledge based on controlled laboratory tests under ideal application conditions. No guarantee of any performance characteristic is therefore given or implied and we do not hold ourselves responsible for any consequential damage of whatsoever nature that may arise from use of our products. In the event of a proven product fault our liability will be limited to the replacement of the product only. It is the user's responsibility to confirm the currency of product data sheets.